



Belgian Road Research Centre
Together for sustainable roads



“Pervious (lean) concrete for sustainable road pavements: first results of the Belgian Be-Drain project”

EUPAVE Workshop on Pervious Concrete Pavements

Elia Boonen (Belgian Road Research Centre)

20th October 2021

General context

- Climate change & integral, sustainable water management




- Pervious concrete as one possible measure (SUDS):
 - Discontinuous grading (no or limited sand fraction)
 - 15-25% void content
 - Water permeability of 10^{-4} – 10^{-2} m/s
 - Compressive strength: 10-25 MPa



History: past research on pervious concrete

- Open, porous concrete as **noise reducing** top layer
 - Pervious concrete composition with polymers for increased strength and freeze-thaw durability
 - **1996:** Test sections of low noise pavements at N255 in Herne
 - Two-lift CRCP with different top layers
 - One in porous concrete 0/7 mm (+ polymers)




Belgian Road Research Centre



Open, porous concrete as noise reducing top layer

- Conclusions from test sections in Herne (1996):
 - Very porous concrete gave best initial results for noise reduction
 - However, similar problems as porous asphalt:
 - Clogging of the voids;
 - Loosing aggregates on the surface.



History: pervious lean concrete as base layer for (water permeable) pavings

- Research by University of Louvain-la-Neuve (UCL), ~2000
- Example of composition in standard tender specifications:

coarse aggregates 6.3/20 mm: 1,130 kg
fine aggregates 2/6.3 mm: 565 kg
cement: minimum 200 kg/m³
water: ± 100 l/m³



Belgian Road Research Centre




EUPAVE Workshop "Pervious Concrete Pavements" - 20/10/2021

Pervious lean concrete: current specifications


- Compressive strength after 90 days, determined on cores:
 - individual value **$W_i \geq 10,0 \text{ MPa}$**
 - average value **$W_m \geq 13,0 \text{ MPa}$**
- Water permeability on cores of 100 cm^2 surface area and 10 cm high:
 - **$k_i \geq k_{i,\min} = 4 \cdot 10^{-4} \text{ m/s}$**
- “Effective” porosity on same type of cores (Wallonia):
 - $P_{i,\min} = 6,5 \%$
 - $P_{m,\min} = 8,0 \%$



Experimental setup to determine the water permeability of porous lean concrete



- Constant or variable water level depending on permeability
- **BRRC:** $\Delta z \approx 1\text{-}2\text{ cm}$, constant head permeameter



Current context in Belgium (2018-...)

- Increased interest & demand for water permeable pavements among which **cast-in-place pervious concrete** (cf. ISCR 2018-Berlin + Belgian road sector)
- Demand for representative compaction method in the lab for **porous lean concrete** (cf. certified mixture for base layers)



Hydromedia @ Holcim



For example: Porous concrete for road pavements

- *Promising application for lightly trafficked areas and public spaces*



Batezini et al. (Brasil)



Vogel et al. (Germany)



Recent testing on pervious lean concrete

- Preliminary testing with pilot sections in collaboration with AC Materials in Puurs, Antwerp (*August 2018*):



- 2 different methods of laboratory compaction tested

Conclusions – test tracks AC Materials

- Vibro-compression \neq representative compaction method



- Double-ring infiltrometer to test in situ permeability?

Recent testing on pervious “road concrete”

- New test tracks with Holcim executed at BRRC premises in Sterrebeek (*August 2019*)



- *Promising experience with several lab testing methods*

Start of prenormative research Be-Drain (1/11/2020-1/11/2022)

- “*Béton (maigre) drainant pour revêtements routiers durables*”
- Problem statement:
 - No general technical guidelines for concrete composition and/or performance requirements for application of pervious concrete as **surface course**
 - Lack of representative test/compaction method for pervious lean concrete as **base layer** in the preliminary lab study (certification)



Be-Drain: porous (lean) concrete for sustainable road pavements



- Belgian prenormative research:
 1. **Technical guidelines, performance requirements and adapted testing methods** for pervious (draining) concrete mixes as a function of:
 - Application (top or base layer)
 - In situ compaction method
 - Functional requirements (comfort, freeze-thaw resistance, ravelling, etc.)
 2. **Recommendations for Belgian standard tender specifications** and possible normalization



Be-Drain: research plan

WP 1 - Literatuurstudie –

Selectie van materialen en proefvoorbereiding.

- Recensie van bestaande technische richtlijnen
- Opname van contact met bedrijven voor commercieel product en overzicht van werven om op te volgen



WP 2 - Beproevingen in het labo

- Optimisation des études de laboratoire
- Studie van andere functionele eigenschappen



WP 3 - In situ validatie

- Opvolging van werven
- Aanleg van proefvakken

WP 4 - Synthese en valorisatie van de resultaten



WP	Sous-tâches	Trimestres							
		1	2	3	4	5	6	7	8
Tâche 1	1.1 Literatuurstudie								
	1.2 Selectie van materialen en proefvoorbereiding								
Tâche 2	2.1 Optimisation des études de laboratoire								
	2.2 Studie van andere functionele eigenschappen								
Tâche 3	3.1 Opvolging van werven								
	3.2 Aanleg van proefvakken								
Tâche 4	Synthese en valorisatie van de resultaten								

Timing : 1/11/2020 - 31/10/2022

Literature review

■ Examples from Germany:




Tabelle 7: Anhaltswerte für die Zusammensetzung von Dränbeton

		Decke DBD 8		Tragschicht DBT 16, 22, 32	
		mit PM	ohne PM	mit PM	ohne PM
		[kg/m³]	[kg/m³]	[kg/m³]	[kg/m³]
Gesteinskörnung	fGK 0/2 ¹⁾	60–100	–	–	–
	fGK 0/1	–	–	150–180 ²⁾	150–180 ²⁾
	oder 0/2	–	–	–	–
	gGK 5/8	1.400–1.500	1.500–1.600	–	–
	gGK 8/16,	–	–	1.500–1.600	1.500–1.600
	8/22 oder 8/32				
Zementfestigkeitsklasse	32,5 R/42,5 N	300–350	300–350	150–300 ³⁾	150–300 ³⁾
Wasser	Frischwasser	40–75 ⁵⁾	85–115	52–73 ⁵⁾	60–90 ³⁾
w/z-Wert (eq)	–	0,25–0,30	0,28–0,33	0,30–0,40	0,30–0,40
Polymer (PM) (z. B. Polymerdispersion)	15–20 M.-% v.Z.	45–70	–	–	–
	10–15 M.-% v.Z.	–	–	15–34	–
Zusatzmittel	FM oder BV	1–3	–	–	–
Kunststofffasern (z. B. PAN, PVA)	Länge 6–12 mm	1–2	–	–	–
Konsistenz (Einbau)	Verdichtungsmaß	1,30–1,34 ⁴⁾ (steif, C1)	1,30–1,34 ⁴⁾ (steif, C1)	1,30–1,45 ⁴⁾ (steif, C1)	1,30–1,45 ⁴⁾ (steif, C1)
Druckfestigkeit	Würfel 150 KL oder Zylinder mit Schlankheit h/d = 1	20–30 MPa	20–30 MPa	10–20 MPa	10–20 MPa

- ¹⁾ Die Verwendung einer polierresistenten feinen Gesteinskörnung (z. B. Quarzsand) ist für die Verbesserung der Griffigkeit von DBD zweckmäßig. Polierversuch (PWS) gemäß den TP Gestein-StB, Teil 5.4.2 (PWS-Wert $\geq 0,55$).
- ²⁾ Die Verwendung von Sand 0/1 oder 0,2 kann vorteilhaft sein.
- ³⁾ Die höheren Werte werden bei der Verwendung von Beton-Recyclingmaterial benötigt.
- ⁴⁾ Die Einbaukonsistenz ist auf das Einbauverfahren abzustimmen.
- ⁵⁾ Der Wasseranteil der PM ist beim Zugabewasser berücksichtigt.

Selection of materials & concrete compositions

■ Base materials:

- Limestone aggregates: 4/6 – 6/10 – 10/14 – 14/20 mm (Holcim)
- CEM III/A 42,5 N LA (CBR-Heidelberg)
- Sand?
- Polymeric admixtures (Sika)

■ Concrete compositions:

- Compo 1 = béton 4/14 (**CS**)
- Compo 2 = **BMD 4/20**
- Compo 4 = béton 4/10 (CS)
- Commercial mixes (construction sites)

480 kg kalksteen 10/14

480 kg kalksteen 6/10

480 kg kalksteen 4/6

250 kg CEM III/A 42,5 N LA

100 kg water

960 kg
6/20

{ 320 kg kalksteen 14/20
320 kg kalksteen 10/14
320 kg kalksteen 6/10
480 kg kalksteen 4/6
200 kg CEM III/A
100 kg water

Testing in the laboratory

- **2.1: Optimisation of lab testing methods**

- ⇒ Representative compaction method

- ⇒ Influence of different parameters:

- Cement content
 - W/C ratio
 - Admixtures
 - (Colour pigments)

- **2.2 Study of other functional properties**




vs.



Lab testing – some first results

- *Most promising compaction method so far =*
« **Proctor allégé** » - « **Proctor light** »: 2 layers - 2,5 kg - Hc 305mm; 56 blows/layer, with:
 - **Coring** after 7 days (D 113 mm, H = 100 mm) 3 échantillons par mélange + rectification
 - Common curing protocol BRRC-CRIC (under water after 3 days)
 - Testing of permeability k + effective porosity [CME 52.20] and Rc28 [NBN EN 12390-3]



Lab results – influence of compaction energy

Type of test	Characteristics of test	Symbol	Dimension	Proctor mould		
				A	B	C
Proctor test	Mass of rammer	m_R	kg	2,5	2,5	15,0
	Diameter of rammer	d_2	mm	50	50	125,0
	Height of fall	h_2	mm	305	305	600
	Number of layers	—	—	3	3	3
	Number of blows per layer	—	—	25	56	22
Modified Proctor test	Mass of rammer	m_R	kg	4,5	4,5	15,0
	Diameter of rammer	d_2	mm	50	50	125,0
	Height of fall	h_2	mm	457	457	600
	Number of layers	—	—	5	5	3
	Number of blows per layer	—	—	25	56	98

Abstract from EN 13286-2

Table 1 — Dimensions of new cylindrical test moulds





Proctor mould	Diameter d_1 mm	Height h_1 mm	Thickness	
			Wall t mm	Base plate r mm
A	100,0 ± 1,0	120,0 ± 1,0	7,5 ± 0,5	11,0 ± 0,5
B	150,0 ± 1,0	120,0 ± 1,0	9,0 ± 0,5	14,0 ± 0,5
C	250,0 ± 1,0	200,0 ± 1,0	14,0 ± 0,5	20,0 ± 0,5
NOTE Annex A gives details of other cylindrical test moulds which may be in current use.				



$$\text{Specific energy} = \frac{\text{mass of rammer} \times \text{height of fall} \times \text{number of blows per layer} \times \text{number of layers} \times \text{gravity}}{\text{volume of mould}}$$


Influence of compaction energy

Combinaison	E-19-272-A	E-19-272-B	E-19-273-C	E-19-273-F	E-19-280-G	E-19-281-H
Fabrication	18/06/2019	18/06/2019	1/08/2019	1/08/2019	1/08/2019	1/08/2019
Eprouvettes	6	6	3	3	3	3
Dame [kg]	2,488	2,488	2,488	4,50	4,50	4,50
Hauteur chute [mm]	305,0	305,0	305,0	457,0	457,0	457,0
Nbr coups par couche	28,0	14,0	56,0	56,0	28,0	14,0
Nbr de couches	1,	1,	1,	2,	2,	2,
Pesanteur [N/kg]	9,810	9,810	9,810	9,810	9,810	9,810
Diamètre moule [mm]	152,50	152,50	152,50	152,0	152,0	152,0
Hauteur moule [mm]	126,50	126,50	126,50	126,0	126,0	126,0
Volume [mm³]	2310575	2310575	2310575	2286376	2286376	2286376
Energie spécifique [MJ/m³]	0,090	0,045	0,180	0,988	0,494	0,247




Lab results – Rc versus permeability

DRUKSTERKTE POREUZE BETON (LABO - 28D) - PROCTOR ALLÉGÉ (VARIATION E/C)



Waterdoorlatendheid poreuze betonkernen Variation E/C




Compo 1 with 100l water
= good compromise:

- $R_{c,avg} \geq 20 \text{ MPa}$
- $k_{avg} \geq 4 \cdot 10^{-4} \text{ m/s}$

Other testing in the lab/on site

■ Workability?

- EN 12350-4 (Waltz)
- EN 12350-3 (VeBe)



■ Fluidity/workability period?

- EN 13286-45 "Proctor différé"





Figure 1 — Determination of W_{pc} by compacting method





In situ validation – exemple of site in Herzele

- Different compaction methods experimented by the contractor + 2 different concrete mixes (C = 200 and 230 kg/m³)
- Samples taken on site by BRRC (PA + OPM)...



... and comparison with cores from the pavement



Functional properties in the lab



- E.g. Adapted freeze-thaw testing method

Tableau 5 : Résultats des gel-dégels sur les éprouvettes E-20-924.

N° échantillon	Surface d'essai A mm ²	S _n				
		[kg/m ²]				
		7 cycles	14 cycles	28 cycles	42 cycles	56 cycles
E-20-924/1	10400	0.06	0.34	0.56	1.10	2.08
E-20-924/2	10400	0.02	0.16	0.42	0.68	1.16
E-20-924/3	10400	0.02	0.10	0.56	1.00	2.08

Tableau 6 : Résultats des gel-dégels sur les éprouvettes E-20-927.

N° échantillon	Surface d'essai A mm ²	S _n				
		[kg/m ²]				
		7 cycles	14 cycles	28 cycles	42 cycles	56 cycles
E-20-927/1	10400	0.00	0.10	0.42	1.04	1.56
E-20-927/2	10400	0.00	0.02	0.04	0.04	0.06
E-20-927/3	10400	0.00	0.02	0.12	0.16	0.26




Conclusions & perspectives

Pervious (lean) concrete as promising solution for sustainable water management in urban areas

More experience & improved technical guidelines in Belgium under development:
from base layer to surface course

Current focus on functional properties of pervious concrete pavement





Belgian Road Research Centre
Together for sustainable roads



Elia Boonen, M.Sc. Eng., PhD

Belgian Road Research Centre – Deputy Head of Division
Concrete Roads – Geotechnics – Drainage and Infiltration
Technics Division

T +32 2 766 03 41 – +32 477 94 38 21

E e.boonen@brrc.be

W www.brrc.be